

WITH LTE

ZONE 1/21



IS910.1

The IS910.1 is the tablet for use in ATEX zones 1/21. The 8" tablet is highly robust, powerful and offers many technical advantages: 8.400 mAh Battery, 2 GHz octa-core processor, NFC, Android™ 7.1 etc.

TECHNICAL FEATURES

| | | | | |
|--|---|--|--|---|
| ATEX Zone 1/21 Ⓜ II 2G Ex ib IIC T4 Gb Ⓜ II 2D Ex ib IIIC T135°C Db IP6X | IECEx approval: EX-zone 1/21 Ex ib IIC T4 Gb Ex ib IIIC T135°C Db IP6X | Approved for North America Class I, II Division 1 Group A, B, C, D, E, F, G T4 Intrinsically Safe | approved for Russia | Android 7.1 |
| 4G (LTE) GSM 850/900/1800/ 1900 MHz WCDMA 850/900/1900/ 2100 MHz | Wi-Fi® IEEE 802.11 ac/b/g/n; 13 channels (all) | Bluetooth® 4.1 LE | MSM8953 (Octa-Core 2 GHz), internal memory 16 GB ROM and 2 GB RAM | size: 235 x 154 x 23 mm, weight: 875 g |
| external memory microSD up to 64 GB | 2 cameras: 8 MP rear camera and 2 MP front camera | Near Field Communication | | |

FURTHER FEATURES

| | | | | |
|--|---|---|-------------------------------------|----------------------|
| waterproof: 1 hour up to 2 m, impervious to dust and micropar- ticles | operation range from -20 °C to 60 °C | 8" (20.32 cm) F HD RugDisplay-Glass multi capacitive touchscreen with a resolution of 1080 x 1920 px | usable with gloves | 8.400 mAh battery |
| GPS, AGPS Support, GLONASS | G-Sensor, gyroscope, pressure, humidity, temperature, magnetic- sensor | Push to talk (optional) | Loneworker protection (optional) | IR-camera (optional) |

CONTENTS

Tablet with integrated battery, USB cable i.safe PROTECTOR, charger, quick start manual and safety instructions